



Försättsblad till skriftlig tentamen vid Linköpings Universitet

(fylls i av ansvarig)

Datum för tentamen	<i>Nov. 1, 2013</i>
Sal	<i>G33, G35, G36, G37</i>
Tid	<i>14-18</i>
Kurskod	<i>TDTS06</i>
Provkod	<i>TEN1</i>
Kursnamn/benämning	Computer networks
Institution	<i>IDA</i>
Antal uppgifter som ingår i tentamen	<i>10+1=11</i>
Antal sidor på tentamen (inkl. försättsbladet)	<i>1+1+4=6</i>
Jour/Kursansvarig	<i>Niklas Carlsson</i>
Telefon under skrivtid	<i>013-282644</i>
Besöker salen ca kl.	<i>15:00 and 17:00</i>
Kursadministratör (namn + tfnr + mailadress)	<i>Madeleine Häger Dahlqvist 013-282360, madha@ida.liu.se</i>
Tillåtna hjälpmedel	<i>Dictionary from an official publisher. Hardcopy; not electronic.</i>
Övrigt (exempel när resultat kan ses på webben, betygsgränser, visning, övriga salar tentan går i m.m.)	<i>Grades: 5(36/40); 4(28/40); 3(20/40)</i>
Vilken typ av papper ska användas, rutigt eller linjerat	<i>Your choice.</i>
Antal exemplar i påsen	

TDTS06 – Computer Networks

Final Examination: 14:00-18:00, Friday, November 1, 2013

Time: 240 minutes

Total Marks: 40

Grade Requirements: three (20/40); four (28/40); and five (36/40).

Assistance: None (closed book, closed notes, and no electronics)

Instructor: Niklas Carlsson

Instructions:

- Read all instructions carefully (including these)!!!! Some questions have multiple tasks/parts. Please make sure to address *all* of these.
- The total possible marks granted for each question are given in parentheses. The entire test will be graded out of 40. This gives you 10 marks per hour, or six minutes per mark, plan your time accordingly.
- This examination consists of a total of 10+1=11 questions. Check to ensure that this exam is complete.
- When applicable, please explain how you derived your answers. Your final answers should be clearly stated.
- Write answers legibly; no marks will be given for answers that cannot be read easily.
- Where a discourse or discussion is called for, be concise and precise.
- If necessary, state any assumptions you made in answering a question. However, remember to read the instructions for each question carefully and answer the questions as precisely as possible. Solving the *wrong* question may result in deductions! It is better to solve the *right* question incorrectly, than the *wrong* question correctly.
- Please write your AID number, exam code, page numbers (even if the questions indicate numbers as well), etc. at the top/header of each page. (This ensures that marks always can be accredited to the correct individual, while ensuring that the exam is anonymous.)
- Answers can be provided in either English or Swedish. (If needed, feel free to bring a dictionary from an official publisher. Hardcopy, not electronic!! Also, your dictionary is not allowed to contain any notes; only the printed text by the publisher.)
- Good luck with the exam.

1) Question: Forwarding (6)

Show, illustrate, and explain the path of (i) the *first GET request* and (ii) the *first GET response* between a Web client (browser) and a Web server. You can make the following assumptions:

- The client machine uses Ethernet, has a single interface with a MAC address AA:BB:AA:BB:AA:BB.
- The GET request is for a webpage: www.aa.com/index.html.
- The client has obtained a dynamic IP address 111.222.111.222 from a DHCP server, which itself has IP address 111.222.111.001 and MAC address DD.DD.DD.DD.DD.DD.
- The client uses a local DNS server with IP address 111.222.001.001 and MAC address DD.EE.DD.EE.DD.EE.
- The MAC and IP addresses of the Web server are DD:AA:DD:AA:AA:DD and 196.222.111.111. Similar to the client, the server has a single interface.
- The gateway router closest to the client has four interfaces. The first is the interface closest to the client and has MAC and IP addresses BB:BB:BB:BB:BB:AA and 111.222.111.1. The second interface has MAC and IP addresses BB:BB:BB:BB:BB:BB and 111.222.111.2. The third interface has MAC and IP addresses BB:BB:BB:BB:BB:CC and 111.222.111.3. Finally, the fourth interface has MAC and IP addresses BB:BB:BB:BB:BB:DD and 111.222.111.4.
- The gateway router closest to the server has four interfaces. The first is the interface closest to the server and has MAC and IP addresses CC:CC:CC:CC:CC:AA and 196.222.111.1. The second interface has MAC and IP addresses CC:CC:CC:CC:CC:BB and 196.222.111.2. The third interface has MAC and IP addresses CC:CC:CC:CC:CC:CC and 196.222.111.3. Finally, the fourth interface has MAC and IP addresses CC:CC:CC:CC:CC:DD and 196.222.111.4.
- The forwarding table at the gateway router closest to the client has many entries. However, for this question, the four most closely related entries for each interface states 196.222.0.0/16 over interface 2, 196.222.110.0/25 over interface 3, 196.222.0.0/18 over interface 4, and 196.222.64.0/18 over interface 2.
- The forwarding table at the gateway router closest to the server has many entries. However, for this question, the four most closely related entries for each interface states 111.222.192.0/16 over interface 2, 111.222.0.0/17 over interface 3, 111.222.128.0/19 over interface 4, and 111.222.0.0/25 over interface 2.

In addition to the above answers, you should also draw a picture of the topology and clearly state any assumptions you make about the topology (including parts of the networks not explained above) or anything else needed to solve the question. As with all your answers it is important that you also explain how you derived your answer. For example, why was the packet taking this particular route and not some other route?

2) Question: Encapsulation (4)

Consider the same scenario as above (Q1). Show and illustrate the link-layer frame and encapsulated information for the first *GET response* message when it reaches the network interface card (link layer) of the *client*. You do not have to show all the details of the different headers; however, you should (i) specify what protocols the different headers are associated with, and (ii) provide the address information associated with the source and destination fields for each of the different headers contained within this frame.

3) Question: DHCP, ARP and DNS (4)

Consider the same scenario as above (Q1+Q2). Please show the sequence of Dynamic Host Configuration Protocol (DHCP), Address Resolution Protocol (ARP), and Domain Name System (DNS) messages that was required for the client to obtain all the IP and MAC addresses that it used when sending the HTTP GET request to the Web server. Also, please indicate what address information was included in each of these messages.

4) Question: TCP slow start (4)

Consider the download of the above file *index.html*, located on the server hosting *www.aa.com*. Assume that the client and server are using non-persistent HTTP/1.0, and that there is a 200ms round trip time (RTT) between them. Draw a figure and explain the entire communication sequence associated with the file download, including the TCP handshake and connection teardown. You can assume that the payload is 20 packets, each packet can be sent in 1ms, and that the twelfth (12) payload packet is lost. For simplicity, you can assume that the TCP version is implementing fast retransmit, initially have $ssthresh = 4$, and the timeout period is (approximately) constant at 500ms. You should include a figure that clearly show when each packet is sent and received.

5) Question: HTTP and replication (6)

Performance and personalized service are important aspects of building good Web services. To improve performance when downloading multiple objects from the same server, pipelined HTTP can be used. Please draw a picture illustrating the communication sequence when the client above downloads a smaller version of the above file *www.aa.com/index.html*, which in this question is only 5KB, but the webpage also include four embedded images. The main document and two of the embedded images can be found on the original Web server *www.aa.com* and the final two embedded images can be found on the server *www.bb.com*. Furthermore, both the servers and the client communicate with pipelined HTTP. Your picture should illustrate the client, its local DNS server, all involved Web servers, and the communication sequence. Your picture should also clearly show connection establishment and teardown messages, as well as any other messages needed for the file transfer. You can assume that the HTML page and each of the images are 5KB each, the MSS is 1.5KB, and both webservers have the same RTT and loss rates to the client. Also, how many packets are being sent between each of the two servers and the client? Which of the two servers is likely to be active for the longest period of time?

6) Caching and end-to-end delay (6)

HTTP caches play an important role in networks. Assume that the ISP of the client above (e.g., Q1) has installed a cache in its network. Assume that the RTT to the cache is 5ms and the RTT to the server *www.aa.com* is 200ms. Furthermore, assume that the average client in the ISPs network have an average RTT of 150ms to a representative sample set of Webpages that these clients access.

- Estimate how much improvement in the download time you will obtain at a cache hit of *www.aa.com/index.html* (i.e., when downloading the content from the cache instead of from the server).
- Estimate how much improvement in the average RTT the average client in the ISPs network will see after such installation. For this question you can assume that after the initial warm-up period (when the cache initially is empty) the cache will see an average hit rate of 40%.
- How much bandwidth will the cache help the ISP to save? In addition to the above assumptions, please consider two cases. First assume that the hit rate of all file sizes is the same. Second, and perhaps more realistically, assume that the hit rate is smaller for large files than small files.

7) Question: Distance vector routing (4)

Consider a node A with neighbors B, C, and D. Node A currently has the distance table below. (Note that the network currently is not in a very good shape, and a few routing table updates will be needed to get the network back into shape.) Assume that it receives an updated distance vector from neighbor B which looks as follows [∞ , 0, 2, 3, 4, 2, 8] and an updated distance vector from neighbor C which looks as follows [∞ , 3, 0, 4, 8, 3, 5] . First, update the table below, including A's own distance vector. Second, assume that poison reverse is implemented, and show and explain exactly what information the node sends to each its neighbors (after the table has been updated).

Destination	Costs			
	A (via)	B	C	D
A	0 (A)	∞	∞	∞
B	1 (B)	0	4	2
C	1 (C)	2	0	7
D	1 (D)	3	5	0
E	? (?)	7	8	4
F	? (?)	2	12	9
G	? (?)	11	5	7

8) Question: Wireless power save mode (2)

Illustrate and explain how the power save mode in 802.11 can be used to save energy of the mobile nodes. What is the role of the access point?

9) Question: Packet losses and UDP-based streaming (2)

Give a concrete example how interleaving can be used to handle packet losses in video streaming? Please use a figure to illustrate.

10) Question: BitTorrent (2)

Please explain what incentive BitTorrent provides peers to upload pieces to others?

11) Bonus question: BGP routing (4)

Consider the following information visible to a Border Gateway Protocol (BGP) router in an Autonomous System (AS) A.

- There are four neighboring ASes: B, C, D, and E.
- AS A's internal path costs to the closest gateway routers of each of these three ASes are 2, 3, 5, and 7, respectively.
- A is a customer of B and C; A is peering with D and E.
- For prefix 11.22.0.0/20 AS A sees the following route announcements: B Y Z; C F Z; D Q P Z; and E R Z.
- The last web request that a client located within AS A did to a server located in AS B, C, D, E had a RTT of 25ms, 35ms, 45ms, and 55ms, respectively.
- The last traceroute that somebody in AS B performed to a server or router in AS Z required 13 router hops. The corresponding numbers for traceroute queries between ASes C-Z, D-Z, and E-Z are 12, 15, and 14, respectively.

Please (i) draw a picture of the topology, as seen by AS A, (ii) show and carefully explain how the particular entry for the above prefix would look in the router's forwarding table, and (iii) clearly *list and order* the information that is being used when determining this routing table entry. Note that the order should clearly reflect the priority (and order) used in making the routing decision (and similar routing decisions).

Good luck!!