

1) Question: Forwarding (6)

Show, illustrate, and explain the path of (i) the *first HTTP request* and (ii) the *first HTTP response* between a Web client (browser) and a Web server. You can make the following assumptions:

- The client is located in Sweden and the server in USA.
- Trump is the president in the USA.
- The client machine uses Ethernet, has a single interface with a MAC address AA:AA:AA:AA:AA:AA.
- The GET request is for a webpage: www.aa.com/index.html.
- The client has obtained a dynamic IP address 213.187.213.123 from a DHCP server, which is running on the closest gateway router.
- The client uses a local DNS server with IP address 213.187.128.1 and MAC address EE.EE.EE.EE.EE.EE.
- The MAC and IP addresses of the Web server are DD:DD:DD:DD:DD:DD and 229.222.111.111. Similar to the client, the server has a single interface.
- The gateway router closest to the client has four interfaces. The first is the interface closest to the client and has MAC and IP addresses B1:B1:B1:B1:B1:B1 and 213.187.211.1. The second interface has MAC and IP addresses B2:B2:B2:B2:B2:B2 and 213.187.212.2. The third interface has MAC and IP addresses B3:B3:B3:B3:B3:B3 and 213.187.213.3. Finally, the fourth interface has MAC and IP addresses B4:B4:B4:B4:B4:B4 and 213.187.214.4.
- The gateway router closest to the server has four interfaces. The first is the interface closest to the server and has MAC and IP addresses C1:C1:C1:C1:C1:C1 and 228.222.111.1. The second interface has MAC and IP addresses C2:C2:C2:C2:C2:C2 and 228.222.111.2. The third interface has MAC and IP addresses C3:C3:C3:C3:C3:C3 and 228.222.111.3. Finally, the fourth interface has MAC and IP addresses C4:C4:C4:C4:C4:C4 and 228.222.111.4.
- The forwarding table at the gateway router closest to the client has many entries. However, for this question, the four most closely related entries states: 229.0.0.0/8 over interface 2, 228.0.0.0/9 over interface 3, 229.128.0.0/6 over interface 4, and 229.222.0.0/18 over interface 4.
- The forwarding table at the gateway router closest to the server has many entries. However, for this question, the four most closely related entries states: 213.187.192.0/18 over interface 2, 213.187.208.0/20 over interface 2, 213.187.64.0/18 over interface 3, and 213.187.211.0/25 over interface 4.

For this question, you should also draw a picture of the topology, clearly indicate the path taken by the packet in this topology, and clearly state any assumptions you make about the topology (including parts of the networks not explained above) or anything else needed to solve the question. As with all your answers it is important that you also explain how you derived your answer. For example, why was the packet taking this particular route and not some other route?

2) Question: Encapsulation (4)

Consider the same scenario as above (Q1). Please use figures to show and illustrate the link-layer frame and encapsulated information for:

1. the first *DNS reply* message when it reaches the network interface card (link layer) of the *client*; and
2. the *SYN* message when it reaches the (on the gateway) *outgoing* network interface card (link layer) of the *gateway closest to the server*.

You do not have to show all the details of the different headers; however, you should provide a figure that clearly (i) specify what protocols the different headers are associated with, and (ii) provide the address information associated with the source and destination fields for each of the different headers contained within these two frames (i.e., address information at all layers, including the application layer).

3) Question: TCP slow start (4)

Consider the download of the above file *index.html*, located on the server hosting *www.aa.com*. Assume that the client and server are using non-persistent HTTP/1.0, and that there is a 150ms round trip time (RTT) between them. Please draw a figure and explain the entire communication sequence associated with the file download, including the TCP handshake and connection teardown. You can assume that the payload is 22 packets, that each packet can be sent in 1ms, and that the #4 and #5 (4th and 5th) payload packets are lost. You can also assume that the TCP version is implementing fast retransmit and fast recovery, that the initially *ssthresh* value is 16, and that the timeout period is (approximately) constant at 250ms. You should include a figure that clearly show when each packet is sent and received.

4) Question: HTTP and replication (6)

Performance and personalized service are important aspects of building good Web services. Please draw a picture illustrating the communication sequence when the client above downloads a smaller version of the above file *www.aa.com/index.html*, which in this question is only 7KB, but the webpage instead include a total of six embedded images. The main document and three of the embedded images can be found on the original Web server *www.aa.com* and the final three embedded images can be found on the server *www.bb.com*. You can assume that no proxy cache is used and the client communicates directly with the server *www.aa.com* using *pipelined HTTP* and directly with the server *www.bb.com* using *persistent connections but without pipelining*. Your picture should illustrate the client, all involved Web servers, and the communication sequence. Your picture should also clearly show connection establishment and teardown messages, as well as any other messages needed for the file transfer, so as to capture the relative timing of the different messages taking place over the different connections. You can assume that the HTML page and each of the images are 7KB each, the MSS is 1.5KB, and both webservers have the same RTT and no losses takes place during the example scenario. Also, how many packets are being sent between each of the two servers and the client? Which connections are likely to terminate last?

5) Question: Distance vector routing (4)

Consider a node A with neighbors B, C, and D. Node A currently has the distance table below. (Note that the network currently is not in a very good shape, and a few routing table updates will be needed to get the network back into shape.) Assume that it receives an updated distance vector from neighbor B which looks as follows $[\infty, 0, 1, 4, 8, 4, 4]$ and an updated distance vector from neighbor C which looks as follows $[\infty, 2, 0, 7, 2, 8, 3]$. First, update the table below, including A's own distance vector. Second, assume that poison reverse is implemented, and show and explain exactly what information the node sends to each its neighbors (after the table has been updated).

Destination	Costs			
	A (via)	B	C	D
A	0 (A)	∞	∞	∞
B	1 (B)	0	4	2
C	1 (C)	2	0	8
D	2 (D)	7	4	0
E	? (?)	6	8	6
F	? (?)	3	12	3
G	? (?)	9	4	5

6) Question: Wireless (4)

Draw 3 pictures showing 2 stations sharing a channel using time, frequency and code multiple access (TDMA, FDMA, CDMA).

7) Question: Routing (4)

- Please explain the main difference between forwarding and routing.
- What are the main advantages/disadvantages of link state vs. distance vector routing?
- Give examples of both link state and distance vector protocols.

8) Question: SSL/TLS (4)

Please draw a picture that shows location of TLS in the protocol stack. Does HTTPS use symmetric or asymmetric keys to encrypt the traffic? Also, please draw a picture and use it to explain how the used key(s) is/are obtained?

9) Question: SDN (4)

Explain what Software Defined Networking (SDN) is using a picture that shows a controller and two switches using the OpenFlow protocol. Also, please show a typical path taken (a) by the first packet of a flow and (b) later packets. The controller is running a firewall application. Finally, clearly show the interfaces (APIs) and location of control and data planes.

Good luck!!